

Amendments to the Claims

1-39. (Cancelled)

40. (New) A digital signal recording medium having an area storing an audio title set (ATS), the audio title set (ATS) including data representing a digital audio signal resulting from steps including (1) quantizing a first original audio signal at a first quantization word length and a first sampling frequency, (2) quantizing a second original audio signal into a quantization-resultant audio signal at a second quantization word length and a second sampling frequency, and (3) subjecting the quantization-resultant audio signal to a bit shift, the first original audio signal being in a front channel (Lf,Rf) group having multiple channels, the second original audio signal being in a rear channel (Ls,Rs) group having multiple channels, the first sampling frequency being assigned to each of the channels in the first channel group, the second sampling frequency being assigned to each of the channels in the second channel group, the bit shift having a quantity common to the channels in the second channel group;

the audio title set (ATS) including data representing the first quantization word length and first sampling frequency and the second quantization word length and second sampling frequency, data representing the quantity of the bit shift and channel assignment information for identifying the channels in the first channel group and the channels in the second channel group.

41. (New) A signal encoding apparatus comprising:

means for generating information; and

means for formatting the information into a data structure;

wherein the data structure has an area containing an audio title set (ATS), the audio title set (ATS) including data representing a digital audio signal resulting from

steps including (1) quantizing a first original audio signal at a first quantization word length and a first sampling frequency, (2) quantizing a second original audio signal into a quantization-resultant audio signal at a second quantization word length and a second sampling frequency, and (3) subjecting the quantization-resultant audio signal to a bit shift, the first original audio signal being in a front channel (Lf,Rf) group having multiple channels, the second original audio signal being in a rear channel (Ls,Rs) group having multiple channels, the first sampling frequency being assigned to each of the channels in the first channel group, the second sampling frequency being assigned to each of the channels in the second channel group, the bit shift having a quantity common to the channels in the second channel group;

the audio title set (ATS) including data representing the first quantization word length and first sampling frequency and the second quantization word length and second sampling frequency, data representing the quantity of the bit shift and channel assignment information for identifying the channels in the first channel group and the channels in the second channel group.

42. (New) An apparatus for decoding the digital audio signal recorded on the digital signal recording medium of claim 40, the audio signal being in the first channel group and the second channel group, the apparatus comprising:

means for generating the data representing the first quantization word length and the first sampling frequency and the second quantization word length and the second sampling frequency, the data representing the quantity of the bit shift, and the channel assignment information for identifying the channels in the front channel group and the channels in the rear channel group; and

means for decoding the digital audio signal in the front channel group and the rear channel group in response to the first quantization word length and the first sampling frequency, the second quantization word length and the second sampling frequency, the quantity of the bit shift, and the channel assignment information.


43. (New) A player for reproducing audio contents from the digital signal recording medium of claim 40 which stores the audio signal in the front channel group and the rear channel group, the player comprising:

means for generating the data representing the first quantization word length and the first sampling frequency and the second quantization word length and the second sampling frequency, the data representing the quantity of the bit shift, and the channel assignment information for identifying the channels in the front channel group and the channels in the rear channel group;

means for decoding the digital audio signal in the front channel group and the rear channel group in response to the first quantization word length and the first sampling frequency, the second quantization word length and the second sampling frequency, the quantity of the bit shift, and the channel assignment information; and

means for implementing digital-to-analog conversion of the decoding-resultant audio signal to recover a corresponding analog audio signal.

Respectfully submitted,



Louis Woo, Reg. No. 31,730
Law Offices of Louis Woo
717 North Fayette Street
Alexandria, Virginia 22314
Phone: (703) 299-4090

Date: Jan 30 2004